

特徴 Feature

- 難燃材 (UL94 V-0適合) を使用。(C-30-CS-1~4・7~11-EP-UL)
- パネルの穴にワンタッチでセット
- 非移行性ゴム (汚染試験 JIS K6267 異常なし)
- Flame-retardant rubber (conforms to UL94 V-0) is used. (C-30-CS-1~4・7~11-EP-UL)
- Can be attached one-touch to the hole of a panel.
- Non-transmutation rubber. (No abnormalities with JIS K6267 stain test)

仕様

- 材 質: C-30-CS-1~4・7~11-EP-UL / エチレンプロピレンゴム (EPDM)
- C-30-CS-5・6 / ポリエチレン (PE)

用途

- 小型分電盤の扉のクッション用計測機器のゴム脚

納期

- 標準在庫品

備考


- シロキ酸ガスを抜いたシリコン製も製作します。
- 他のカラーも製作します。(CS-5・CS-6は除く)
- ニトリルゴム製 (NBR) で適用板厚1mm用・1.2mm用も製作します。(C-30-CS-7~10)

Speci-

- Material: C-30-CS-1~4・7~11-EP-UL: Ethylene propylene rubber (EPDM)
- C-30-CS-5・6: Polyethylene (PE)

Specific-

- For small distribution board doors and measuring equipment.

参考パネル穴明け寸法
Reference panel drilling dimensions

C-30-CS-1-EP-UL



C-30-CS-2-EP-UL



C-30-CS-3-EP-UL



C-30-CS-4-EP-UL




C-30-CS-5




C-30-CS-6


〔C-30-CS-1-EP-UL〕




〔C-30-CS-2-EP-UL〕




〔C-30-CS-3-EP-UL〕




〔C-30-CS-4-EP-UL〕




〔C-30-CS-5〕




〔C-30-CS-6〕




〔C-30-CS-7-EP-UL〕




〔C-30-CS-8-EP-UL〕




〔C-30-CS-9-EP-UL〕



〔C-30-CS-10-EP-UL〕



〔C-30-CS-11-EP-UL〕



商品番号 Product No.	RoHS 10	φd	硬 度 Hardness	製品質量(g) Mass	コード Code
C-30-CS-1-EP-UL	●	17	50° ±5°	7.5	24103
C-30-CS-2-EP-UL	●	9.2	70° ±5°	3.35	24104
C-30-CS-3-EP-UL	●	8.2		0.9	24105
C-30-CS-4-EP-UL	●	5.4	50° ±5°	0.5	24106
C-30-CS-5	●	8.8	67Dスケール	0.9	20257
C-30-CS-6	●	8.8	67D scale	1.4	20258

● : RoHS10指令対応品

▲ : RoHS10指令に対応可能です。

商品番号 Product No.	RoHS 10	φd	硬 度 Hardness	製品質量(g) Mass	コード Code
C-30-CS-7-EP-UL	●	4.8		0.4	24107
C-30-CS-8-EP-UL	●	6.2		0.6	24108
C-30-CS-9-EP-UL	●	7.8	50° ±5°	1.0	24109
C-30-CS-10-EP-UL	●	9.4		1.3	24110
C-30-CS-11-EP-UL	●	5.4		0.6	25175

● : RoHS10指令対応品

▲ : RoHS10指令に対応可能です。