

K-800-1

鉄製

モニターアーム 一段型モニターアーム SINGLE-STAGE MONITOR ARMS

対応モニタはVESA規格75mm×75mm
または100mm×100mm



K-800-1

商品番号 Product No.	RoHS 10	製品質量 (g) Mass	コード Code
K-800-1		3,100	31605

● : RoHS10指令対応品 ▲ : RoHS10指令に対応可能です。

特徴 Feature

- アームは上下63° 左右360°、モニターの首振りは上下95° 左右60° の位置で保持します。
- スプリングによるバランサー方式です。
- 本製品は5kgのモニターに合せて設定しています。
- Arm moves 63° vertically and 360° horizontally, monitor tilts 95° and swivels 60°, and is able to maintain position.
- Spring-loaded balance mechanism.
- This product is adjusted to accommodate a 5kg monitor.

仕様

- 材質 : 本体/電気亜鉛めっき鋼板(SEC)
軸部/ステンレス鋼板(SUS304)
カバー/ABS樹脂
台座/ポリアセタール(POM)

用途

- 医療機器・コンピュータ周辺機器・工作機械

納期

- 標準品・・・納期お問合せください

備考

- 取付け用ブラケットなども状況に合わせて製作します。
- 図面の製品は重量5kgのモニター用として設定しています。
- 金属の摩擦抵抗による静止ですので、規定荷重の操作感に±15%程度の違いが発生します。ご了承ください。
- 先端部に取付けるモニターの荷重によって、反力調整の変更が可能です。お問合せください。



Speci- fications

- Material: Body: Electro-galvanized steel plate (SEC)
Shaft: Stainless steel plate (SUS304)
Cover: ABS resin
Base: Polyacetal (POM)

Specifi- cation

- Medical Equipment, Computer Peripherals, Machine Tools

Remarks

- The product pictured is designed to mount a 5kg monitor.
- Stops due to metal frictional resistance, so an error of about ±15% in the operation sensitivity of the rated load may arise. Please be aware of this fact.
- Reaction force can be adjusted for the weight of the monitor to be mounted on the front. Contact us for details.

